



General Information

The Sandvik QA440 builds upon the success of the smaller QA340 by delivering true static screen productivity in a durable, mobile package.

Designed with maximum productivity to the fore, the QA440 incorporates a large feed hopper, a pair of large screen boxes and extended conveyors that afford massive stockpiling capabilities.

This highly productive machine is also carried on a large, durable chassis that is designed to withstand the rigours of a large quarry or recycling application.

A self-loading hydraulic bogie provides an independent transport capability without the need for low loaders.

The operational flexibility of the Sandvik QA440 is enhanced by an exceptionally wide range of optional extras. These include vibrating and tipping grids, mild steel hopper liners, overband magnet, and a reversible side conveyor.

- Unique, independent 6 x 1.5m (20' x 5') equivalent Doublescreen box design allows for precision screening, but huge screening area enables high volume production
- Capable of working alongside large jaw crushers, yet precise enough to produce accurate aggregate products
- Modern chassis design ensures in-built machine quality and strength for maximum up-time
- Fully tracked for on-site mobility
- Available with optional vibrating grid
- Capable of operating in the most hostile environments
- Massive stockpiling capability through integrated hydraulic conveyors
- Easily transported from site to site
- Global aftermarket support, with standard stock parts to ensure minimum loss of production
- Machine design designed for optimum fuel economy and low operating costs.



	QA440
Hopper	
Capacity	7.5m ³ / 9.8yd ³
Maximum Capacity	11.33m ³ / 14.8yd ³
Type	Hydraulically Tipping Grid
Grid Area	2200x3600mm / 87x142"
Grid Area With Sides Raised	2200x4400mm / 87x173"
Tipping Grid Angle Standard	96°
Tipping Grid Angle Vibrating Grid	34°
Feed Conveyor Belt	
Width	1200mm / 47"
Length	3699mm / 145"
Motor	160cc
Gear box Ratio	R 20:1
Head Drum Ø	332mm / 13"
Tail Drum Ø	270mm / 10.5"
Main Conveyor	
Width	1000mm / 39"
Length	12390mm / 488"
Drive Drum Ø	282mm / 11"
Tail Drum Ø	270mm / 10.5"
Motor	490cc
Screen	
Type	2 Bearing
Decks	2 Deck
First screen box size	3048 x 1524mm / 120 x 60"
Second screen box size	3048 x 1524mm / 120 x 60"
Tensioning System	Ratchet
Speed	1200rpm
Throw	7.24mm
Motor	49.1cc
Side Conveyors	
Discharge Height	5000mm / 197"
Width	700mm / 27.5"

Options

Hopper Hardox Liner Plates Back & Sides
 Central Auto Lube (conveyors/screen)
 Dust Suppression Including Canvas Covers
 Remote Diesel Pump
 Water Pump
 -20°C / -4F Arctic Package
 -30°C / -22F Arctic Package
 Tropical / High ambient package
 Double Deck Vibrating Grid

	QA440
Drive	Hydraulic motor 395cc
Head Drum	228mm / 9"
Tail Drum	216mm / 8.5"
Length	10551mm / 415"
Fines Conveyor	
Discharge Height	4560mm / 179"
Width	1200mm / 47"
Drive	Hydraulic motor 395cc
Head Drum	228mm / 9"
Tail Drum	216mm / 8.5"
Length	7976mm / 314"
Tracks	
Length	3800mm / 150"
Width	500mm / 19.5"
Power Pack	
Engine Power	2012 75kw / 100hp
Diesel Tank Size	290litres / 76.5USG
Hydraulic Tank Size	370litres / 98USG
General Technical Data	
Transport dimensions	
Length	17810mm / 58.4'
Width	2890mm / 9.5'
Height	3840mm / 12.6'
Operating dimensions	
Length	18210mm / 59.7'
Width	18380mm / 60.3'
Height	6680mm / 21.9'
Standard Weight	30460kg / 67,200lbs
Performance	
Max Feed Size	200mm / 8"
Capacity (up to)	600 MTPH / 661 STPH
Travel Speed	1.06 K/H / 0.66 MPH
Max slope climbing	20°
Max slope side to side	10°

Hardox Spreader Plate
 Screening Media
 Double Shaft Shredder unit
 Weigh Scale
 Side Conveyor Feed Boot Hardox Lined
 Lighting Masts
 Overband magnet & frame
 Wheeled Dolly

The units depicted show all options currently available, and the colour scheme reflects the eventual scheme to be used. Current models may differ from those featured in this brochure. Please contact Sandvik to clarify specification and options. The material in this brochure is of general application for information and guidance only, and no representation or warranty is made or given by the manufacturer that its products will be suitable for a customer's particular purpose and enquiry should always be made of the manufacturer to ensure such suitability. Whilst reasonable efforts have been made in the preparation of this document to ensure its accuracy, the manufacturer assumes no liability resulting from errors or omissions in this document, or from the use or interpretation of the information contained herein. The manufacturer reserves the right to make changes to the information in this brochure and the product design without reservation and without notification to users.

SANDVIK MINING AND CONSTRUCTION (UK) HEARTH COTE ROAD SWADLINCOTE DERBYSHIRE DE11 9DU ENGLAND
 TEL +44 (0)1283 212121 FAX +44 (0) 1283 217342 info.extec-fintec@sandvik.com www.miningandconstruction.sandvik.com

