



3.- TECHNICAL DATA

3.1.- TECHNICAL SPECIFICATIONS

TYPE OF MACHINE		HC-2/50 AA
Pressure force:	Tm	50
Pressure:	Bar	415
Total Power:	Kw	20
	CV	27
Motors:	Kw	18.5 + 1.5
	CV	25 + 2
Voltage:	V	380
Frequency:	Hz	50
Hydraulics Brand:		"REXROTH"
Number of Pumps:		1
Main Pumps:	L/min.	96 + 36
Auxiliary Pumps:	L/min.	9
PLC:		"SIEMENS"
Chamber Height and Width:	mm	700 x 800
Bale size, H x W x Length:	mm	720 x 830 x VARIABLE
Real Feed Opening:	mm	740 x 1550
Specific pressure:	Kg/cm ²	8.93
Weight of machine:	Kp	7000
General Dimensions, W x Length x H:	mm	2100 x 7400 x 4000
Quantity of ties:		4
Strapping system:		AUTOMATIC
Type of strapping:		AA5
Strapping of Element:		ANNEALED WIRE Ø=3.2
Type of Oil:		UNIL HF046
Hydraulic oil volume:	L	430
Press Cylinder:	mm	DE – 115/150 x 1880
Pincer Cylinder:	mm	SE – 110/160 x 80
Strapping input Cylinder:	mm	DE – 30/50 x 210
Cut Cylinder:	mm	DE – 35/60 x 60